

# **FLYING CRAFT CAMERA AND SENSOR MECHANIZED LIFT PLATFORM**

## **FIELD OF THE INVENTION**

This invention relates to flying craft. More particularly this invention relates to a mechanized lift platform that extends and retracts a device for capturing images, sounds and data, individually and collectively, from a flying craft to include but not limited to airplanes, helicopters, blimps, hot air balloons and space crafts. This invention has particular applicability to cameras and sensors installed in flying craft.

## **BACKGROUND OF THE INVENTION**

Flying craft are utilized to capture images, sounds and data, individually and collectively. Aerial image, sound and datum capturing devices include cameras and sensors. Aerial cameras and sensors are affixed to the flying craft either internally or externally. Internal cameras and sensors are mounted to the structure inside the body of the flying craft. Internally mounted cameras and sensors are able to capture images, sounds and data using a window, retractable door or permanent opening in the flying craft. Internally mounted cameras and sensors have minimal if any exposure to the environment outside the flying craft. In contrast, external cameras and sensors are mounted to the exterior structure of a flying craft. An externally mounted camera is subject to the

environment outside the flying craft at all times. Both internally and externally mounted cameras and sensors uses include but are not limited to surveillance, reconnaissance, monitoring, surveying, broadcasting and motion pictures.

Both internally mounted and externally mounted cameras and sensors are limited by their respective installations. The internally mounted camera has a limited field of view. The flying craft interior structure will obstruct image capturing during lateral rotation of the camera. Furthermore, interior arrangement modifications to accommodate a camera or sensor inside the body of a flying craft create a single function aircraft.

Externally installed cameras and sensors have a specific set of limitations. Externally mounted cameras and sensors affect aerodynamic properties of the flying craft at all times. The change in aerodynamic properties resulting from an externally mounted device reduces flying craft performance and increases structural stress and fatigue. Furthermore, aerial cameras and sensors are expensive. Flying craft with externally mounted cameras and sensors must be parked in a secured area to prevent damage and deter theft. Under the current political environment there is a requirement to conceal cameras and sensors from the public and/or foreign governments. The mechanized lift platform proposed in this document satisfies this requirement.

What is needed is a method of aurally capturing images, sounds and data collectively or individually, by combining the functionality of the internally and externally mounted cameras. What is needed is a mechanism that can extend a camera and sensor outside the flying craft for full field of view and retract the

camera and sensor inside the body of the aircraft upon completion of image, sound and/or datum collection to maximize the flying craft performance. What is needed is a flying craft that can be used to capture images, sounds and data and transport passengers and freight.

## **OBJECTS OF THE INVENTION**

It is an object of this invention to disclose an improved method of aerially capturing images, sounds and data. It is an object of this invention to disclose a mechanized lift platform that extends and retracts a camera and sensor, individually or collectively, from a flying craft. It is an object of this invention to disclose a method to create a multi-role flying craft that is able to aerially capture images, sounds and data and efficiently transport cargo and passengers. It is yet a further objective of this invention to disclose an improved method of aerial photography, video, sound collection and multimedia that is concealed from the public's view.

One aspect of this invention provides for a method of aerially capturing images, sounds and data comprising the steps of: Providing a device for extending a camera and sensor outside a flying craft whereby the camera and sensor can be completely retracted into the aircraft, having a platform structure to mount a camera and sensor, an electric motor to provide power, mechanized liner motion structure installed in flying craft to stabilize and guide the camera and sensor mounting platform during extension and retraction, concealment doors to open and close, relay switches to the flying craft cockpit and/or cabin

to operate the lift platform and concealment doors; and opening the concealment doors and extending the camera and sensor during flight to collect images, sounds and data or any combination thereof and upon completion of camera and sensor activities, retracting the lift platform inside the aircraft and closing the concealment doors.

Another aspect of this invention provides for a method of aerial photography, video, sound collection and multimedia and transmitting said captured images, sounds and data to a graphical display comprising the steps of: Providing a device for extending a camera and sensor outside a flying craft whereby the camera and sensor can be completely retracted into the aircraft, having a platform structure to mount a camera and sensor, an electric motor to provide power, mechanized liner motion structure installed in flying craft to stabilize and guide the camera and sensor mounting platform during extension and retraction, concealment doors to open and close, relay switches to the flying craft cockpit and/or cabin to operate the lift platform and concealment doors, multimedia viewing and recording equipment connected to camera and sensor; and opening the concealment doors and extending the camera and sensor during flight to collect images, sounds and data or any combination thereof and display said collected images in a live graphical display in aircraft or to a remote site and upon completion of camera and sensor activities, retracting the lift platform inside the aircraft and closing the concealment doors.

A preferred aspect of this invention provides for a method of creating a multi-role aircraft comprising the steps of: Providing a device for

extending a camera and sensor outside a flying craft whereby the camera and sensor can be completely retracted into the aircraft, having a platform structure to mount a camera and sensor, a motor to provide power, mechanized linear motion structure installed in flying craft to stabilize and guide the camera and sensor mounting platform during extension and retraction, concealment doors to open and close, relay switches to the flying craft cockpit and/or cabin to operate the lift platform and concealment doors; and opening the concealment doors and extending the camera and sensor during flight to collect images, sounds and data or any combination thereof and upon completion of camera and sensor activities, retracting the lift platform inside the aircraft and closing the concealment doors such that the camera will be hidden from public view and the original flying craft speed, maneuverability, aerodynamic characteristics and cabin configuration are not altered.

Various other objects, advantages and features of this invention will become apparent to those skilled in the art from the following description in conjunction with the accompanying drawings.

## **FIGURES OF THE INVENTION**

Figure 1 is a perspective view of a flying craft with the camera/sensor mechanized lift platform in the fully extended position. Figure 2 is a perspective view of the camera/sensor mechanized lift platform. Figure 3 is a model of the lift platform giving reference to individual components that comprise the whole unit.

The following is a discussion and description of the preferred specific embodiments of this invention, such being made with reference to the drawings, wherein the same reference numerals are used to indicate the same or similar parts and/or structure. It should be noted that such discussion and description is not meant to unduly limit the scope of the invention.

## **DESCRIPTION OF THE INVENTION**

Now turning to the drawings and more particular to figure 1 we have a side view of the lift mechanism installed into an aircraft. This installation is in the tail section, however the mechanism can be installed at any location on the craft. A method of installation comprises the steps of: (1) the lift mechanism (2) a concealment door (3) motor drive (4) mounting surface for the equipment or camera. Figure 2 shows the lift mechanism using a motor drive system that can be powered by an electric motor, hydraulics, pre-stressed springs, air drive or magnetic drive. Figure 3 shows that the lift mechanism is mounted to existing structure in the flying craft. The mechanism uses parallel sliding rails to control the platform that the camera is mounted to during the movement of the camera from the stowed position to the operating position. The mechanism uses a drive system that is attached to the platform to power the camera into position.